

About

BioClean SafeStep[™] Overshoes have low levels of particle shedding and are processed to ensure ISO Class 5 compatibility. They feature an elastomer coating to ensure good grip and durability.

Specifications

TEARING STRENGTH: 1.6kg (min)

MATERIAL: Elastomer coating over non-woven spunbonded polypropylene

MATERIAL: Elastomer coating over non-woven spunbonded polypropylene

THICKNESS: 0.14mm

THICKNESS: 0.14mm

HEIGHT: 170mm (6.5")

LENGTH: 406mm (16") and 455mm (18").

COMPATIBILITY: ISO Class 5

CONSTRUCTION: Elastomer coating over non-woven spun bonded polypropylene. Tearing Strength: 1.6kg (min).

COLOUR: White

Features

- Slip-resistant
- Low levels of particle shedding
- Durable
- Elastomer coating

BIOCLEAN™ SAFESTEP™ Cleanroom Overshoes NSO

ISO CLASS 5 COMPATIBLE

SLIP-RESISTANT & DURABLE

LOW-LINTING



Quality Standards

- Manufactured in a facility holding ISO 9001:2008 certification
- Processed in an NEBB certified ISO Class 5 cleanroom environment

Physical Properties



Shelf Life & Storage

Five (5) years from date of manufacture. Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

PRODUCT CODE	LENGTH(±5%)	HEIGHT(±5%)	Conductivity
NSO016	406mm	170mm	N/A
NSO018	457mm	170mm	

TO ORDER

Re-order code	Size
NSO016 NSO018	16" (406mm) 18" (457mm)

Packing

100 pieces per sealed inner PE bag; one inner bag per sealed outer PE bag; four outer bags per lined carton (400 pieces)

CONTACT

Europe

(Headquarters)

Nitritex Ltd. Minton Enterprise Park, Oaks Drive, Newmarket, Suffolk, CB8 7YY, United Kingdom T: +44 (0) 1638 663338 F: +44 (0) 1638 668890 E: <u>europe@bioclean.com</u>

Other Regions

Asia: <u>malaysia@bioclean.com</u> Americas: <u>americas@bioclean.com</u>

Nitritex Beyond Critical Supplies

BioClean[™] is a brand of Nitritex Ltd. For more information, please visit<u>www.bioclean.com</u>

NSO/1711/PDS26